

Blackmagic URSA Cine 12K



Blackmagic URSA Cine 12K is a revolution in digital film with a new large format RGBW 36 x 24mm sensor with larger photo-sites for 16 stops of dynamic range. This revolutionary model also includes interchangeable lens mounts, a dedicated assist station with a second 5" HDR LCD touchscreen, built in ND filters and industry standard Lemo and Fischer connections. Blackmagic URSA Cine comes with a massive 8TB of removable high performance media storage built in and also includes high speed 10G Ethernet and Wifi for fast media upload and syncing to Blackmagic Cloud.

€13 625

Caratteristiche

Dimensione effettiva del sensore

35.64mm x 23.32mm (Large Format)

Attacco obiettivo

PL mount. Interchangeable with URSA Cine lockable EF mount included.

Controllo obiettivo

Active EF and PL mount lens control with compatible lenses.

Gamma dinamica

16 Stops

Risoluzioni di ripresa

12,288 x 8040 (12K 3:2 open gate)
 12,288 x 6480 (12K 16:9)
 12,288 x 6912 (12K 17:9)
 12,288 x 5112 (12K 2.4:1)
 9648 x 8040 (12K 6:5)
 9408 x 6264 (9K 3:2)
 8688 x 4896 (9K 16:9)
 9312 x 4896 (9K 17:9)
 9312 x 3864 (9K 2.4:1)
 7680 x 6408 (9K 6:5)
 8192 x 5360 (8K 3:2 open gate)
 8192 x 4608 (8K 16:9)
 8192 x 4320 (8K 17:9)
 8192 x 3408 (8K 2.4:1)
 6432 x 5360 (8K 6:5)
 4096 x 2680 (4K 3:2 open gate)
 4096 x 2304 (4K 16:9)
 4096 x 2160 (4K 17:9)
 4096 x 1704 (4K 2.4:1)
 3216 x 2680 (4K 6:5)

Frame rate

Project frame rates of 23.98, 24, 25, 29.97, 30, 50, 59.94 and 60 fps supported. Maximum sensor frame rate dependent on resolution selected.

Frame rate elevati compatibili

12K 3:2 open gate up to 80 fps
 12K 17:9 up to 100 fps
 12K 2.4:1 up to 120 fps
 9K 3:2 Super 35 up to 100 fps
 8K / 4K 3:2 open gate up to 144 fps
 8K / 4K 2.4:1 up to 224 fps

Filtri ND integrati

Button activated ND filters with clear, 2-stop, 4-stop and 6-stop IR ND filters.








Messa a fuoco

Focus button turns on peaking, auto focus available using compatible lenses.

Diaframma Iris wheel and touchscreen slider for manual iris adjustment on electronically controllable lenses, iris button for instant auto iris settings on compatible lenses so no pixel is clipped in film mode. Scene average auto exposure in video mode. Screens 2 x Monitoring Screens 1 x Camera Status Screen Monitoring Screen Dimensions 5 inch. Monitoring Screen Resolution 1920px x 1080px	Monitoring Screen Brightness 1500 nits. Monitoring Screen Type LCD capacitive touchscreen Supporto per metadati Automatically populated lens data from i/Technology with compatible PL, LPL lenses and electronic EF lenses when using optional EF lens mount. Automatic recording of camera settings and slate data such as project, scene number, take and special notes.	Controlli Touchscreen menus on 5 inch screen. Push buttons for other controls. 7 assignable shortcut keys plus 6 assignable shortcut keys on URSA Cine EVF. Timecode Highly accurate timecode clock. Less than 1 frame drift every 8 hours.
---	---	---

Connessioni

Uscite video 2 Trasmissione SDI 1.5G, 3G, 6G, 12G. Ingressi audio analogico 2 x XLR analog switchable between mic, line and AES audio. Phantom power support. Uscite audio analogico 1 x 3.5mm headphone jack	Ingressi di riferimento Tri-Sync/Black Burst and Timecode. Viewfinder 1 x Viewfinder USB-C with power, data, video and locking connector. Accessori 1 x 7-pin Lemo 'EXT' for power out, serial communication, and run/stop. 1 x 3-pin Fischer 'RS' for power out and run/stop.	Interfaccia computer 2 x USB Type-C side expansion ports for camera accessories. Software updates using rear side USB-C. Ethernet 1 x 10Gb/s RJ-45 connector supporting 10/100/1000/10G BASE-T for Web Media Management, Blackmagic Cloud uploads, camera control and streaming.
---	--	--



Audio

Microfono

Integrated stereo microphone.

Speaker integrato

1 x mono speaker.

Standard

Standard video SD

No

Standard video HD

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60, 1080i50,
1080i59.94, 1080i60

Standard video Ultra HD

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

Conformità alla norma SDI

SMPTE 292M, SMPTE 424 Level B,
SMPTE 2081-1, SMPTE 2082-1

Campionamento audio SDI

48 kHz and 24 bit

Media

Media

1 x Blackmagic Media Module.

Formattazione

Blackmagic

Codec compatibili

Codec

Blackmagic RAW, bitrate costante 3:1,
Blackmagic RAW, bitrate costante 5:1,
Blackmagic RAW, bitrate costante 8:1,
Blackmagic RAW, bitrate costante
12:1,
Blackmagic RAW, bitrate costante
18:1,
Blackmagic RAW, qualità costante Q0,
Blackmagic RAW, qualità costante Q1,
Blackmagic RAW, qualità costante Q3,
Blackmagic RAW, qualità costante Q5.
H.264 Proxy in 1920 x 1080, 8-bit
4:2:0

Controllo

Controllo esterno

Blackmagic URSA Cine EVF can trigger record plus camera functions assigned to the VF1, VF2, VF3, Zoom, Exp and Record buttons. External Camera Control supported using REST API over Ethernet, WiFi or serial communication via the 7-pin Lemo connector. Run / Stop supported via 3-pin Fischer and 7-pin Lemo connector. Blackmagic iPad control and Bluetooth control supported. Blackmagic Zoom Demand and Blackmagic Focus Demand for controlling camera and compatible lenses.

Streaming

Streaming diretto

Supports Secure Reliable Transport (SRT) and Real Time Messaging Protocol (RTMP) local live streaming using a Ethernet or WiFi, or global live streaming using an internet connection via Ethernet, WiFi or USB-C cellular data.

Gestione rete

NTP

Network time protocol support allows you to sync the time on your camera, whenever connected to a network with any NTP server of your choice.

FTP

Download files from any drive attached to your camera using FTP.

Web Media Manager

Using a browser connected over Ethernet, web media manager allows you to access, browse, download and delete files from any drive connected to the camera.

SMB

File sharing using SMB

Archiviazione

Tipo di archiviazione

1 x Blackmagic Media Module 8TB

Frequenze di archiviazione

Storage rates based on 24 frames per second.

12K - 12,288 x 8040

Blackmagic RAW 3:1 - 1,194 MB/s

Blackmagic RAW 8:1 - 448 MB/s

Blackmagic RAW 12:1 - 298 MB/s

Blackmagic RAW 18:1 - 199 MB/s

Blackmagic RAW Q0 - 298 a 1,432 MB/s

Blackmagic RAW Q1 - 179 a 716 MB/s

Blackmagic RAW Q3 - 119 a 298 MB/s

Blackmagic RAW Q5 - 90 a 224 MB/s

9K - 9408 x 6264

Blackmagic RAW 3:1 - 713 MB/s

Blackmagic RAW 8:1 - 268 MB/s

Blackmagic RAW 12:1 - 178 MB/s

Blackmagic RAW 18:1 - 119 MB/s

Blackmagic RAW Q0 - 178 a 856 MB/s

Blackmagic RAW Q1 - 107 a 428 MB/s

Blackmagic RAW Q3 - 71 a 178 MB/s

Blackmagic RAW Q5 - 54 a 134 MB/s

8K - 8192 x 5360

Blackmagic RAW 3:1 - 533 MB/s

Blackmagic RAW 5:1 - 320 MB/s

Blackmagic RAW 8:1 - 200 MB/s

Blackmagic RAW 12:1 - 133 MB/s

Blackmagic RAW Q0 - 133 a 319 MB/s

Blackmagic RAW Q1 - 80 a 200 MB/s

Blackmagic RAW Q3 - 53 a 133 MB/s

Blackmagic RAW Q5 - 40 a 100 MB/s

4K - 4096 x 26896 x 2680

Blackmagic RAW 3:1 - 135 MB/s

Blackmagic RAW 4:1 - 101 MB/s

Blackmagic RAW 5:1 - 81 MB/s

Blackmagic RAW 6:1 - 68 MB/s

Blackmagic RAW Q0 - 34 a 81 MB/s

Blackmagic RAW Q1 - 20 a 50 MB/s

Blackmagic RAW Q3 - 13 a 34 MB/s

Blackmagic RAW Q5 - 10 a 25 MB/s

Formati di registrazione

Blackmagic RAW 3:1, 8:1, 12:1, 18:1,

Q0, Q1, Q3 and Q5 at full sensor

width or height resolutions:

[12,288 x 8,040], [12,288 x 6,912],

[12,288 x 6,480], [12,288 x 5,112] and

[9,648 x 8,040]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 8:1, 12:1, 18:1,

Q0, Q1, Q3 and Q5 at Super 35

windowed sensor resolutions:

[9,408 x 6,264], [8,688 x 4,896],

[9,312 x 4,896], [9,312 x 3,864] and

[7,680 x 6,408]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 5:1, 8:1, 12:1,

Q0, Q1, Q3 and Q5 at full sensor

width or height scaled to:

[8,192 x 5,360], [8,192 x 4,608],

[8,192 x 4,320], [8,192 x 3,408] and

[6,432 x 5,360]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 4:1, 5:1, 6:1, Q0,

Q1, Q3 and Q5 at full sensor width or

height scaled to:

[4,096 x 2,680], [4,096 x 2,304],

[4,096 x 2,160], [4,096 x 1,704] and

[3,216 x 2,680]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Constant Quality Rates for 12K and 9K are: Q0 12:1 - 2.5:1, Q1 20:1 - 5:1, Q3 30:1 - 12:1, Q5 40:1 - 16:1

Constant Quality Rates for 8K and 4K are: Q0 12:1 - 5:1, Q1 20:1 - 8:1, Q3 30:1 - 12:1, Q5 40:1 - 16:1

Actual storage rates are dependent on image subject matter.

Software

Software inclusi

URSA Cine Blackmagic OS
DaVinci Resolve Studio for Mac and Windows including activation key
Blackmagic Camera Setup
Blackmagic RAW Player
Blackmagic RAW QuickLook Plugin
Blackmagic RAW SDK

Sistemi operativi



Mac 13.0 Ventura,
Mac 14.0 Sonoma o successivo



Windows 10 e 11

Requisiti di alimentazione

Alimentazione

+24V DC external power supply 100 -
240 AC 50/60Hz compatible with IEC
C14 socket.
Molex connector for rear
battery plate.

Ingresso per alimentazione esterna

1 x 8 pin socket for external power or
battery use.
B-Mount battery plate.

Power Output

1 x 7-pin Lemo with +12V DV or +24V
DC power output depending on
camera supply.
1 x 3-pin Fischer with +12V DV or
+24V DC power output depending on
camera supply.
B-Mount battery plate with 2-pin
Lemo +12V regulated output
from camera.

Accessori

Accessori opzionali

Blackmagic URSA Cine EVF
Blackmagic URSA Cine Mount PL
Blackmagic URSA Cine Mount LPL
Blackmagic URSA Cine Mount EF
Blackmagic URSA Cine Mount Shims
Blackmagic URSA Cine Battery Plate B Mnt
Blackmagic URSA Cine Battery Plate Gold
Blackmagic URSA Cine Battery Plate VLock
Blackmagic URSA Cine Baseplate 15
Blackmagic URSA Cine Baseplate 19
Blackmagic URSA Cine Handle
Blackmagic URSA Cine Grips
Blackmagic URSA Cine 5" LCD Sunshade
Blackmagic Media Dock
Blackmagic Media Module 8TB
Blackmagic Media Module CF
Blackmagic Video Assist 7" 12G HDR
Blackmagic Video Assist 5" 12G HDR
Blackmagic Video Assist 7" 3G
Blackmagic Video Assist 5" 3G
ATEM Streaming Bridge

Specifiche fisiche



Specifiche ambientali

Temperatura operativa
0° to 40°C (32° to 104°F)

Temperatura di stoccaggio
-20° to 45°C (-4° to 113°F)

Umidità relativa
0% to 90% non-condensing

Il prodotto include

Blackmagic URSA Cine 12K Body
Blackmagic URSA Cine Mount PL (installed)
Blackmagic URSA Cine Mount EF and screws
Blackmagic Media Module 8TB
URSA Cine Handle and bolts
URSA Cine Top Rod Mount 15
URSA Cine Baseplate 19
Plastic folding screen hood for 5" assist station
URSA Cine Battery Plate B Mount
WiFi Antennas
URSA Cine PL Body Cap
URSA Cine EF Body Cap
Rubber caps for connectors
+24V DC 250W power supply
DaVinci Resolve Studio with activation key
Wallet di benvenuto con codice QR per scaricare il software
Blackmagic Sticker
Custom foamed Pelican 1510 case

Garanzia

12 Month Limited
Manufacturer's Warranty.

Tutti gli elementi su questo sito web sono protetti dal copyright Blackmagic Design Pty. Ltd. 2024, tutti i diritti riservati. Tutti i marchi appartengono ai rispettivi proprietari. Il prezzo di vendita suggerito dal produttore esclude tasse di vendita e costi di spedizione. Questo sito web utilizza servizi di remarketing per mostrare annunci pubblicitari su siti web di terze parti dopo aver visitato il nostro sito. Puoi disattivare questa funzione in qualsiasi momento cambiando le impostazioni dei cookie. [Informativa sulla privacy.](#)

Rivenditore autorizzato di Blackmagic Design