

RODE LAVALIER-II Specs

Key Specs	
Microphone Type	Lavalier
Polar Pattern	Omnidirectional
Frequency Range	20 Hz to 20 kHz
Maximum SPL	106 dB SPL RMS (Plug-In Power, 1% THD) 120 dB SPL RMS (Plug-In Power, 10% THD)
Output Connector	1x 1/8" / 3.5 mm TRS Male (on Attached Cable)
Power Sources	Plug-In Power
Color	Black

Microphone

Microphone Type	Lavalier
Sound Field	Mono
Element Type	Condenser
Polar Pattern	Omnidirectional

Performance

Frequency Range	20 Hz to 20 kHz
Maximum SPL	106 dB SPL RMS (Plug-In Power, 1% THD) 120 dB SPL RMS (Plug-In Power, 10% THD)
Sensitivity	-38 dBV/Pa at 1 kHz
Dynamic Range	79 dB (Typical)

Connectivity

Output Connector	1x 1/8" / 3.5 mm TRS Male (on Attached Cable)
Cable Length	46.1" / 117 cm

Power

Power Sources	Plug-In Power
Operating Voltage	1.5 to 5 V (Plug-In Power)

Physical

Color	Black
Dimensions	H: 0.2 x W: 0.4 x L: 1.2" / H: 5 x W: 10 x L: 30.5 mm (Microphone) H: 0.2 x W: 0.4 x L: 47.2" / H: 5 x W: 10 x L: 1200 mm (Mic and Cable)
Weight	0.3 oz / 9 g (Microphone) 0.4 oz / 12 g (with Mount, with Windscreen)