

Key Specs	
Display Size	7.0" / 17.8 cm
Native Resolution	1920 x 1200
Touchscreen	Yes
HDR Support	Yes: Advanced HDR
Video I/O	1x HDMI 2.0 Input 1x BNC (3G-SDI) Input 1x HDMI 2.0 Loop Output Show More
Media/Memory Card Slot	Single Slot: SD/SDHC/SDXC [LUT/Firmware Update Only]
Video Format	HDMI (8/10-Bit 4:2:2) DCI 4K: 60/59.94/50/30/29.97/25/24/23.98 UHD 4K: 60/59.94/50/30/29.97/25/24/23.98 Show More
Battery	2x L-Series Mount on Fixed Plate

Display

Panel Type	IPS-Type LCD
Display Size	7.0" / 17.8 cm
Native Resolution	1920 x 1200
Aspect Ratio	16:10
Touchscreen	Yes
Maximum Brightness	2200 nits / cd/m ²
Color Support	1.07 Billion Colors (10-Bit)
HDR Support	Yes: Advanced HDR
Color Gamut	100% Rec. 709
LUT Support	Yes

Image Controls	Anamorphic De-Squeeze, Blue Only, False Color, Focus Peaking, Histogram, Pixel-to-Pixel Zoom, RGB Parade, Screen Markers, Vectorscope, Waveform, Zebra
----------------	--

Inputs/Outputs

Antenna I/O	2x RP-SMA
Video I/O	1x HDMI 2.0 Input 1x BNC (3G-SDI) Input 1x HDMI 2.0 Loop Output 1x BNC (3G-SDI) Output
Embedded Audio	HDMI: 8-Channel SDI: 12-Channel
Audio I/O	1x 1/8" / 3.5 mm Line Input 1x 1/8" / 3.5 mm Headphone Output
Built-In Speaker	No
Power I/O	1x Barrel (16.8 VDC) Input
Other I/O	1x 2.5 mm (LANC) Output 1x USB-C 3.0 / 3.1/3.2 Gen 1 Input [Shared with Power, Camera Control] 2x USB-C 3.0 / 3.1/3.2 Gen 1 Output
Media/Memory Card Slot	Single Slot: SD/SDHC/SDXC [LUT/Firmware Update Only]

Wireless

Wireless Range	984.3' / 300 m
Frequency Range	5 GHz
Latency	60 ms
Wi-Fi	Wi-Fi 6E (802.11ax)
Bluetooth	No
Mobile App Compatible	No

Format Support

Video Format	HDMI (8/10-Bit 4:2:2) DCI 4K: 60/59.94/50/30/29.97/25/24/23.98 UHD 4K: 60/59.94/50/30/29.97/25/24/23.98 DCI 2K: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/29.97/25/24/23.98 1080i: 60/59.94/50 720p: 60/59.94/50 SDI (8/10-Bit 4:2:2) DCI 2K: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/30/25/24/23.98 1080i: 60/59.94/50 720p: 60/59.94/50
Video Signal Conversion	HDMI to SDI 1080p SDI to HDMI 1080p
Audio Format	8-Channel 24-Bit

Power

Input Power	6.2 to 16.8 VDC
Battery	2x L-Series Mount on Fixed Plate
Power Consumption	13 W (Maximum)

Mounting

Tripod/Accessory Mounting	Top 1x 1/4"-20 Female Bottom 1x 1/4"-20 Female
---------------------------	---

General

Environmental Resistance	No
Operating Conditions	Up to 104°F / 40°C
Material of Construction	Plastic
Dimensions	7.8 x 5.2 x 1.5" / 198 x 133 x 39 mm
Weight	1.3 lb / 580.00 g